

**TÁPEGYÉG 1 FÁZIS, 24 VDC DIMENSION
C SZÉRIA, GENERATION 2**

24-28 V DC, 5 A

CP5.241

PSU 100-240V ac I/P 24V dc 5A 120W O/P

- Kimeneti áramerősség 5A
- 32 mm-es szélesség
- Fémház
- 20 % teljesítménytartalék
- Hiccup Plus

**TERMÉKLEÍRÁS****MŰSZAKI ADATOK**

| | |
|---|-----------|
| Active Transient | Igen |
| Clamp type | Csavar |
| Conformal coated | Nem |
| DC relay output | Igen |
| Efficiency At 120 V AC, full load. Typical | 93,6 % |
| Efficiency At 230 V AC, full load. Typical | 94,3 % |
| Efficiency At 230 V AC. Typical | 92 % |
| Fázisok száma | 1 |
| Hold-up time at 120 V AC, full load. Typical. | 35 ms |
| Hold-up time at 230 V AC, full load. Typical. | 35 ms |
| Input current at 230 V ac typical | 6 A |
| Input voltage AC | 100-240 V |
| Input voltage ac max | 264 V AC |
| Input voltage ac min | 85 V AC |
| Input voltage DC | 110-150 V |
| Input voltage dc max | 180 V DC |

| | |
|--|--|
| Input voltage dc min | 88 V DC |
| Input voltage range | Wide-range |
| Inrush current at 120 V ac typical | 5 A |
| IP-osztály | IP20 |
| Jóváhagyások | ATEX, CE, cULus, IECEx, IEC 62368-1:2018 |
| Lifetime at 120 V ac, full load and +40 ° C | 143000 h |
| Lifetime at 230 V ac, full load and +40 ° C | 166000 h |
| Magasság | 124 mm |
| Mélység | 102 mm |
| MTBF (IEC 61709) 230 V AC, Maximum Load, 40 ° C | 876000 h |
| Output Current | 5 A |
| Output voltage | 24 V DC |
| Output voltage max | 28 V DC |
| Output voltage min | 24 V DC |
| Power Consumption At 120 V AC | 1,09 A |
| Power Consumption At 230 V AC | 0,6 A |
| Power Factor at 120 V AC, full load. Typical | 0,98 |
| Power Factor at 230 V AC, full load. Typical | 0,91 |
| Power Reduction Of 60 To 70 ° C | 3 W/°C |
| Ripple. max | 50 mV pp |
| Series | Dimension C |
| Supply Frequency | 50-60 ±6 % |
| Szélesség | 32 mm |
| Teljesítmény | 120 W |
| Temperature Range Without Derating From | -25 °C |
| Temperature Range Without Derating To | 60 °C |
| Tömeg | 0,44 kg |
| Védőanyag | Alumínium |

