



HCW4 - NEM ÉRINTKEZŐ INKREMENTÁLIS ÉRZÉKELŐ

HCW4PG590032G3

- Felbontás max. 1024 P / K
- A, B és Z csatornák és ugyanaz invertálva
- IP67, opcionális IP69K
- 2m kábellel



TERMÉKLEÍRÁS

MŰSZAKI ADATOK

Befoglalási átmérő	50 mm
Csatlakozás	Kábel
Érzékelő típusa	Differenciális
Felbontás	32 P/R
IP-osztály	IP67
Kilépés	Push/Pull
Max. tápfeszültség, DC	30 V DC
Max. üzemi hőmérséklet	85 °C
Min. tápfeszültség, DC	5 V DC
Min. üzemi hőmérséklet	-40 °C

STANDARD CONNECTION

	-	+	A	B	0	A/	B/	G/	Ground
G3	PVC cable 8 wires reference	WH white	BN brown	GN green	YE yellow	GY grey	PK pink	BL blue	RD red
GP	PUR cable 12 wires 8200550	WH white + WH/GR white/green	BL blue + BL/GR brown / green	GY grey	BN brown	RD red	PK pink	GN green	BK black General shielding

ORDERING REFERENCE (Contact the factory for special versions, ex: stainless steel version, connections...)

	Mechanics	Supply Output stage	Signals	Resolution	Connection	Connection orientation
HCW4	00 Modular	PG2 5Vdc TL / RS422 output PG6 5 to 30Vdc Push/Pull output (TL / RS422 available if encoder supply is 24Vdc)	9 A, A/ B, B/ 0, 0/	1024 max	G3 : PVC cable 8 wires GP : PUR cable 12 wires	R020 : Radial cable 2m
Ex: HCW4	00 //	PG6	9 //	01024 //	G3	R020

AVAILABLE RESOLUTIONS

32 64 128 256 1024

